



ONE COAT ONLY HS^{PLUS}

Twice the coverage due to high oil content – saves time and money!



PRODUCT DESCRIPTION

Decorative, satin oil-based protective finish for exterior wood. Micro-porous, allowing the wood to breathe and reduces the risk of swelling and shrinkage. Water-repellent, extremely weather- and UV-resistant. Does not crack, peel or flake.

Easy to renew, no sanding or primer necessary. Easy to apply, does not dry during application.

Osmo One Coat Only HS^{PLUS} with a minimum solvent content, does not contain any biocidal ingredients or preservatives and has an uniquely high solid content, which accounts for its large coverage. It offers maximal surface protection with only one thin coat. When dry, the finish is safe for humans, animals and plants, suitable for children's toys as per EN 71.3 (European norm) and resistant to perspiration and saliva in accordance with DIN 53160 (German industrial norm).

RECOMMENDED USE

Osmo One Coat Only HS^{PLUS} is suitable for any wood in the outdoors: Carports, wooden claddings, balconies, gates, pergolas, garden furniture and summer houses. Especially suitable for renewing old micro-porous glazes.

INGREDIENTS

Based on natural vegetable oils (sunflower oil), iron-oxide and organic pigments, titanium dioxide-white pigment, siccatives (drying agents) and additives. Disaromatised white spirit (benzene-free).

This product fulfils EU regulation (2004/42/EC) ac-

ording to the VOC-content of max. 400 g/l (Cat. A/e (2010)).

Detailed declaration of ingredients upon request.

TECHNICAL DATA

Specific gravity: 1.0-1.2 g/cm³

Viscosity: >70s DIN EN ISO 2431/3 mm, viscous

Odour: Faint/mild, odourless after drying

Flashpoint: >61 °C according to DIN 2719

STORAGE

Up to 5 years and more if can is kept dry and is tightly closed. If thickened by frost, store 24-36 hours under room temperature before usage.

SURFACE PREPARATION

Wood surface must be clean, dry and frost-free (moisture content max. 20 %).

Osmo One Coat Only HS^{PLUS} is ready to use, please do not thin. Stir well before use.

Old micro-porous stains need to be cleaned. Old paints and lacquers must be removed. For sanding works generally wear a dust mask.

The finished surface is, among other things, influenced by the wood's natural characteristics. Basically, a trial application is required, especially for unfamiliar surfaces.

If additional protection against blue stain, rot and mildew is desired, pretreat the wood if possible on all sides with Osmo WR Base Coat*.

*Use biocides safely. Always read label and product information before use.



METHODS OF APPLICATION

Apply thinly with the Osmo Natural Bristle Brush or Osmo Microfibre Roller and streak well, along the wood grain.

Leave to dry, with good ventilation.

CLEANING OF TOOLS

With Osmo Brush Cleaner (free from aromatic compounds).

DRYING TIME

Approx. 12 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time.

COVERAGE

Approx. 26 m² with one coat per litre.

Product coverage depends significantly on the character of the timber. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to reduced coverage.

NOTE

The transparent colour shade will be influenced by the wood's natural colour, causing the result to deviate from the colour shown on the colour chart. If applied to thickly, this product may leave shiny areas. These shiny areas will weather naturally within a short period of time leaving an even, satin appearance.

Light transparent colour shades only offer limited UV-protection (greying and fading because of the sunbeams). Therefore please do not use for surfaces that are heavily exposed to the weather and sun.

In case additional protection in the outdoors is required (e.g. windows, doors), apply a final coat with 1 x Osmo UV-Protection-Oil Clear (410 without biocides or 420 with film protection) after drying. This protects against dirt and increases the durability of the finish. Please use Natural Oil Woodstain White 900 as a top coat for White Spruce 9211.

Some wood species "bleed" natural water-soluble ingredients during weathering.

CAUTION

Keep out of the reach of children. Do not get in eyes, on skin, or on clothing. Contains 2-butanonoxime. May produce an allergic reaction. If medical advice is needed, have product container or label at hand. Use only outdoors or in a well-ventilated area. Dispose of contents/container in accordance with chemical waste disposal regulations (AVV 08 01 11). Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition). The dried finish is classified as B2 (normal flammability) according to DIN 4102 regulations.

Safety data sheet upon request for professional users.

DISPOSAL

Dispose of product residuals and completely emptied packages according to the local official guidelines (EU-waste code key number 08 01 11). Only fully emptied tins can be recycled.

COLOUR TONE

Nr. 9211 White Spruce

Nr. 9212 Silver Poplar

Nr. 9221 Pine

Nr. 9222 Natural Spruce

Nr. 9232 Mahogany

Nr. 9233 Hemlock

Nr. 9234 Scand. Red

Nr. 9235 Red Cedar

Nr. 9236 Larch

Nr. 9241 Oak

Nr. 9242 Fir Green

Nr. 9252 Patina

Nr. 9261 Walnut

Nr. 9262 Teak

Nr. 9264 Rosewood

Nr. 9271 Ebony

CAN SIZES

0.375 l; 0.75 l; 2.50 l; 25 l

The above mentioned information is given to the best of our knowledge but without liability.

Dated: 06/14